



TRISOLV POSTER PAPER PRIME 135 SA GLOSSY

glossy 3685, 310 g/m²

Self-adhesive poster paper for advertising applications, stickers and labels

This multi-coated, weather- and water-proof paper with a gloss finish is suitable for printing with solvent, latex and UV-curing inks. Its waterbased permanent acrylic adhesive adheres to virtually all clean, smooth surfaces and makes it possible to produce custom-designed stickers and labels. Thanks to its water-repellent surface, TriSolv Poster Paper Prime 135 SA can also be used for short- to medium-term outdoor applications. The particularly robust liner makes this paper very good for use in printer/cutters.

Advantages

- Brilliant colour reproduction
- Water-repellent surface
- High colour saturation saves up to 30% of printing inks
- Optimised for use with cutter plotters
- Adheres to clean and smooth surfaces

General tips

Please note when printing with any of the 300 and 500 series HP Latex printer, to print roll to roll!

The ink amounts must be adjusted to the paper. Please reduce the single colors cyan, magenta, yellow and black (ink restrictions) and shorten the maximum amount of ink (ink limit). This will help your costs on inks and improve your drying performance.

Please follow the recommendations of the printer and ink manufacturer. The temperature for preheating and drying the media should be checked previously to make sure you will achieve desired results.

To maintain the high quality of the paper, it should be stored and converted in a climate of 30 – 65 % relative humidity and at a temperature of 10 – 30 °C (50 – 86 °F).

Latex / IR hardening ink is not fully water-resistant.

Technologies



Properties



The values stated above are only for orientation. Before using our print media please check its compatibility for your printer and the intended application. We cannot be held responsible for any mistakes resulting from technical changes in the printing process and with printing components. Product design changes to our products technical developments may be carried out without prior notice.

Physical data

Name	Value	Norm
Weight [g/m ²]	310	ISO 536
Weight (without liner/ adhesive) [g/m ²]	135	ISO 536
Thickness (paper) [μm]	275	ISO 534
Thickness (paper without liner / adhesive) [μm]	150	534
Chromaticity (D50/2°) M0	L* 94.0 a* 0.8 b* -3.7	ISO 13655, M0
Opacity [%]	97	ISO 2471
Adhesion strength on glass (24h) [N/25mm]	20	FTM 1
Adhesion strength on V2A (24h) [N/25mm]	25	FTM 1
Adhesion strength on Forex (24h) [N/25mm]	20	FTM 1
Base	TriSolv Poster Paper Prime 135 Glossy 3684	

The values stated above are only for orientation. Before using our print media please check its compatibility for your printer and the intended application. We cannot be held responsible for any mistakes resulting from technical changes in the printing process and with printing components. Product design changes to our products technical developments may be carried out without prior notice.